



SHB-B95

## 技术参数

Technical Parameter

SHB-B95循环水式真空泵 Circulating water vacuum pump	
功率 Power	370 W
电压 Voltage	220V/60Hz
流量 Flow	80 L/min
扬程 Lift	12 m
最大真空度 Max-vacuum	0.098 (Mpa)
单头抽气量 Pumping volume	10 (L/min)
水箱容积 Volume	50 L
外形尺寸 Size	450 * 340 * 840 mm
重量 Weight	37kg
输出电流 Output current	2.6A

## 主要特点

MAIN FEATURES

- 与台式泵相比，抽气量更大
- 装有脚轮，移动方便，适应实验室，车间灵活配置
- 需定期更换水槽中的水，以保证水质纯净，保证真空度
- 适用于有蒸发，蒸馏，结晶，干燥，升华，过滤减压，脱气等过程的研究性实验，小试，小量生产过程
- Compared with desktop pumps, the pumping capacity is larger
- Equipped with casters, easy to move, adapt to the laboratory, flexible configuration of the workshop
- The water in the sink needs to be replaced regularly to ensure the purity of the water and the vacuum
- Suitable for research experiments, small-scale trials and small-scale production processes involving evaporation, distillation, crystallization, drying, sublimation, filtration and pressure reduction, and degassing



R1050

SHB-B95

S212-100L



SHZ-III

## 主要特点

### MAIN FEATURES

- 特制的流体消声器，减少水中气体，使真空度更高更稳
- 需定期更换水槽中的水，以保证水质纯净，保证真空度
- 可用于抽取腐蚀性气体，需缩短换水周期
- The special fluid muffler reduces the gas in the water and makes the vacuum higher and more stable
- The water in the sink needs to be replaced regularly to ensure the purity of the water and the vacuum
- Can be used to extract corrosive gas, need to shorten the water change cycle

## 技术参数

### Technical Parameter

型号 Model	SHZ-DIII防腐型 Anticorrosive	SHZ-DIII不锈钢型 Stainless steel type	SHZ-DIII四氟型 PTFE type	SHZ-DIII四表四抽型 Multi-table multi-tap
电机功率 Motor Power	180W	180W	180W	250W
工作电源 Power supply	220V50HZ			
流量 Flow	80L/min			
扬程 Lift	10M			
最大真空度 Maximum vacuum	0.098MPa			
抽气头数 Number of pump-heads	2	2	2	4
安全功能 Security function	逆流防止阀 Backflow prevention valve			
水箱容积 Water tank volume	15L	15L	15L	15L
水箱材质 Water tank material	PP			
外形尺寸 Dimensions	385*280*420 mm			

